



ONE MEDIA FOR ALL YOUR NEEDS!

675 Metropolitan Ave  
Suite 4094  
Atlanta, GA 30310  
Phone: (404) 228-6329 x 304  
sales@instantonemedia.com

# PRODUCT SPECIFICATIONS

## IOM 50/50 Perforated Window Vinyl **\$275.00**

SKU: 2110-W

### Key Features & Benefits

- 6 mil polymeric PVC film
- 96# PE-coated silicone release liner
- 50/50 pattern; 1.5mm hole size
- Expected outdoor durability up to 3 years. (Actual results may vary if exposed to extreme conditions).
- Adhesive Removable Clear solvent/acrylic.
- Final tack 48 hours.
- Compatibility: Use with Solvent, Eco, UV and Latex printers. (A pretest is always recommended.)

Properties: Intended for short to medium-term one-way vision vehicle window graphics or store-fronts. White vinyl front with a black back and clear adhesive. Pressure sensitive adhesive is designed for clean removal from glass.

Handling: Avoid touching material or introducing dust and dirt on to print face. This can cause anomalies and artifacts when printed. Always store unused material wound tight in original packaging.

Printing: Suggested Media Setting Universal Self Adhesive Vinyl. Depending on printing platform and RIP software; ink load recommendation: 250%. Make sure that ink is dry when it reaches the take-up reel. An external dryer or heat lamp will accelerate drying. Do not be alarmed if the print looks distorted. This is caused by the backing paper and the image should look correct after the film is removed from the backing paper.

Installation: This material can be applied using a squeegee on a dry surface. The wet-installation method may cause water to become trapped in the perforations. Be sure the surface is clean. Make sure the installed material does not contact any molding or gaskets as this may cause adhesion failure.

Recommended Uses: Vehicle and commercial windows. Certain states have regulations regarding minimal visibility for window graphics.